



Residential • Commercial
Agriculture • Government

PETRIFY™

INDUSTRIAL STRENGTH – WOOD PENETRATING OIL

ONETIME
LIFETIME
TREATMENT

WOOD STABILIZER & PRESERVATIVE

ECO FRIENDLY • 100% NON TOXIC

Termites • Water • Mold • Wood Rot

Use on hard or soft wood, plywood & bamboo • Apply on dry, wet or green wood
Use above or below ground and water • Treat pre or post stain, paint, or varnish

Eliminates cupping, checking, splitting & warping • Repels water, decay, and insects • Fire retardant
Stops expansion and contraction • Eliminates fastener rejection • Long-term protection in temperatures
-0° F to 130° F • Encapsulates copper fungicides on treated woods such as CCA, ACQ for protection

Indoor/Outdoor • 100% Biodegradable • No VOCs

EQUIPMENT: Compression Sprayer-Brush-Roller-Air or Airless paint gun

USES: Fence, Deck/Patio, Dock, Furniture, Construction Framing, Landscape Timber, Barn/Stable/Pens, Playground Equipment, Log Cabins, Doors and Frames, Boats, Woodcraft & Sculpture, Bee Houses, Dog Houses, Cedar Shake Shingles & Siding, and Any Plywood, Wood or Bamboo Structures.

HOW IT WORKS: ONETIME LIFETIME TREATMENT. The ultimate in WOOD PRESERVATION. This dynamic product triggers the early stages of WOOD PETRIFICATION. PETRIFY is a low viscosity PENETRANT, not a coating. In wood, the absence of moisture is the key to preservation. Prior to treatment with PETRIFY, wood contains two types of water. Free water that is harbored in the fiber structure of the wood and bound water which is harbored in the cellular/molecular structure of the wood. The absence of water is the absence of issues. PETRIFY is a non toxic, solvent based formulation that displaces free and bound water when applied to wood. It modifies the molecular make up of the wood, leaving it water, insect, mold and decay resistant from the inside out.

APPLICATION: For best results, apply when wood is wet and in the heat of the day. Apply directly to target area moving slowly and systematically across the surface. Repeat applications will enhance results. Apply to both sides of surface when possible. If prior to construction, submerge lumber in PETRIFY for maximum effectiveness. Paint or Stain can be applied prior to or upon completion of treatment to wood. PETRIFY will not change color of wood. Ensure you have enough liquid to finish the defined area as partial treatment will not produce a ONETIME LIFETIME result.

PATIO, DECK & DOCK: 1 Gallon per 100 sq. ft. (10 x 10) surface area.

FENCE & THIN MATERIAL: 1 Gallon per 200 sq. ft. of surface area.

HORIZONTAL SURFACES: Treat 100 sq. ft. or less at a time. Using a sprayer or wand, hold the nozzle close to the wood and apply the liquid in a spray, slowly moving across the surface. Apply PETRIFY until the surface appears glossy wet and repeat 2-3 times or until the wood appears to resist rapid

penetration. PETRIFY will immediately migrate vertically and horizontally throughout the wood fibers. Ensure you have enough liquid to finish the defined area as partial treatment will not produce a ONETIME LIFETIME result. **FOR ADDED UV SURFACE PROTECTION:** Re-treat the surface with PETRIFY 6-12 months later when absorption will be contained to the top surface area of the wood.

VERTICAL TREATMENTS: Apply to 200 linear ft. or less at a time working from top to bottom. Move on to the next section and repeat. **NOTE:** Keeping the wood surface wet with solution is more difficult than on horizontal areas. The use of a brush or roller may be preferred over a spray nozzle. Application with an airless gun is desirable for large areas. Airless units are available at your local rental store. Request the smallest nozzle available for the gun.

STAIN, PAINT & GLUE: Allow 72 hours cure time for application of oil based or aqueous based stains and paints (oil based is recommended for best results). PETRIFY will not compromise adhesion in wood projects. Adhesives can be applied prior to or upon completion of treatment to wood.

PRECAUTIONS: Provide adequate ventilation when applying in closed areas. Avoid contact with eyes. In case of eye contact, flush with water for at least 15 minutes. After use, wash hands with soap and water. Keep out of reach of children. REGISTRATION EXEMPT FIFRA 25(b). The ingredients used in PETRIFY are classified as Food Grade by the EPA and FDA.

INGREDIENTS: USDA NOP Certified Organic 5% Cedar Oil, Dimethylpolysiloxane 95%

Treat Nature with Nature™

DISTRIBUTED BY: Wondercide LLC, Austin, TX 78704

QUESTIONS OR COMMENTS: 877-TX-ORGANIC wondercide.com



GO TEXAN.

